2 ACRES DRIPLINE ACCESSORIES KIT (WITH 63MM & 75MM PVC PIPES)



Product Configuration

Emitter Spacing	40cms (Also available in 30cms and 50cms)
Maximum Area covered	9000mtrs
Recommended Configuration	Mainline and submain located at the top of the field
Flow rate of emitter	4lph (Also available in 2lph) at 0.8kg/cm2
Maximum running Dripline length per side	70mtrs
Maximum no. of plots	4nos.
Max. Driplines per 2 cocks/plots	3000mtrs
Recommended working pressure	1kg/cm2 near the filter
Maximum permissible pressure	1.5kg/cm2 near the filter
Life of the system	2 to 5years (Depending on the dripline thickness)
Kit to be used with	16mm Driplines and 75mm and 63mm PVC pipes

Kit Contents

Part No.	Description	Qty.	Pictures/ photos
1	2.5" 30mtr3 Screen Filter	1	VANI DR
2	16mm Take off connector +grommet	200	A.
3	17mm Joiners	50	
4	2" Turbo Ventury Injector assembly	1	
5	Drill	1	
6	Pressure Gauge	1	
7	75mm PVC Ball Valve	1	

2 ACRES DRIPLINE ACCESSORIES KIT

(WITH 63MM & 75MM PVC PIPES)



Part No.	Description	Qty.	Pictures/ photos
8	63mm PVC Ball Valve	4	
9	63mm Flush valve	4	
10	75mm Tee	5	
11	75mm FTA	2	
12	75mmx63mm Reducer	4	
13	63mm Elbow	4	
14	PVC Solvent (0.5L)	1	Í

