### 2 ACRES DRIPLINE ACCESSORIES KIT

(WITH 75MM PVC PIPES)



# **Product Configuration**

Emitter Spacing	40cms (Also available in 30cms and 50cms)
Maximum Area covered	9000mtrs
Recommended Configuration	Mainline and submain located at the top of the field
Flow rate of emitter	4lph (Also available in 2lph) at 0.8kg/cm2
Maximum running Dripline length per side	70mtrs
Maximum no. of plots	2nos.
Maximum Driplines per cock/plot	3000mtrs
Recommended working pressure	1kg/cm2 near the filter
Maximum permissible pressure	1.5kg/cm2 near the filter
Life of the system	2 to 5years (Depending on the dripline thickness)
Kit to be used with	16mm Driplines and 75mm PVC pipes

## **Kit Contents**

Part No.	Description	Qty.	Pictures/ photos
1	2.5" 30mtr3 Screen Filter	1	TANI DE
2	16mm Take off connector +grommet	200	A.
3	17mm Joiners	50	
4	2" Turbo Ventury Injector assembly	1	
5	Drill	1	
6	Pressure Gauge	1	
7	75mm PVC Ball Valve	3	

#### 2 ACRES DRIPLINE ACCESSORIES KIT

(WITH 75MM PVC PIPES)



Part No.	Description	Qty.	Pictures/ photos
8	75mm Flush valve	2	
9	75mm Tee	2	
10	75mm FTA	2	
11	75mm Elbow	3	
12	PVC Solvent (0.5L)	1	İ

#### Layout

